

Metal enclosures **BGUK 20**



Picture shows BGUK 30/2

Advantages

Integrated rail system for the installation of different product sizes (BGUK 30 - BGUK 60)
Excellent corrosion protection and high abrasion resistance through powder-coated surface RAL 5008
Ventilation openings for optimized cooling
Faceplate without cooling fins for individual connection options (BGUK 10 - 60)
Integrated crane eyes

Applications

Universal metal enclosure with cooling fins for degree of protection IP20/IP23

Approvals



Metal enclosures BGUK 20

Type		BGUK 20
Electrical data	Operating data	
	Enclosure suitable for protection index	IP 23
	For power (single-phase)*	2,500 VA
	For power (three-phase)*	1500 VA
	Max. Power loss (at 40 °C ambient temperature)	240 W
Notes		The indicated power is a guideline. Deviations may occur depending on the version of the transformer.
*		
Order numbers		
Order Number		BGUK 20

Type		BGUK 20
Mechanical data	Terminal and mounting	
	Floor mounting	Yes
	Wall mounting	Yes
	Cable glanding type	2x M 25
	Cable glanding Ø	9 - 14 mm
Measures and weights		
Effective inside dimension (W)	305 mm	
Effective inside dimension (D)	185 mm	
Effective inside dimension (H)	290 mm	
Fixing hole Ø	9 mm	
Weight		
Weight	12.0 kg	

