

## Metal enclosures **BGUK 30**



Picture shows BGUK 30/2

### Advantages

Integrated rail system for the installation of different product sizes (BGUK 30 - BGUK 60)
Excellent corrosion protection and high abrasion resistance through powder-coated surface RAL 5008
Ventilation openings for optimized cooling
Faceplate without cooling fins for individual connection options (BGUK 10 - 60)
Integrated crane eyes

### Applications

Universal metal enclosure with cooling fins for degree of protection IP20/IP23

### Approvals



## Metal enclosures BGUK 30

Type		BGUK 30
Electrical data	Operating data	
	Enclosure suitable for protection index	IP 23
	For power (single-phase)*	5,000 VA
	For power (three-phase)*	3,000 VA
	Max. Power loss (at 40 °C ambient temperature)	260 W
Notes	The indicated power is a guideline. Deviations may occur depending on the version of the transformer.	
*		
Order numbers		
Order Number		BGUK 30

Type		BGUK 30
Mechanical data	Terminal and mounting	
	Floor mounting	Yes
	Wall mounting	Yes
	Cable glanding type	2x M 25
	Cable glanding Ø	9 - 14 mm
Measures and weights		
Effective inside dimension (W)	305 mm	
Effective inside dimension (D)	185 mm	
Effective inside dimension (H)	370 mm	
Fixing hole Ø	11 x 14 mm	
Weight		
Weight	16.0 kg	

