

## 100 V-line transformer

### **AÜ 100/6 Discontinued line - not for new designs**



Picture shows AÜ 100/10

## Advantages

Solder tab for free wiring

Universally designed for 4, 8 and 16 Ohms

Additional tapings at 3/4, 1/2 and 1/4 output

Very good moisture protection and low noise thanks to BLOCKIMPEX vacuum impregnation

Simple mounting thanks to robust metal fixing rail with oval slots


## Applications

100 Vac transformer for electro-acoustic installations with a 100 Vac transmission circuit.

## Standards

100 V-line transformer  
to DIN EN 60950

## Approvals



# 100 V-line transformer

## AÜ 100/6 Discontinued line - not for new designs



### Electrical data

Type	AÜ 100/6 Discontinued line - not for new designs
Input	
Rated input voltage	0 - 100 Vac
Rated frequency	45 - 15000 Hz
Output	
Output power	6 / 4.5 / 3 / 1.5 W
Impedance	1.6/2.2/3.3/6.6 kΩ
Environment	
Ambient temperature max.	40 °C
Safety and protection	
Type	Open type
Insulation class	E
Protection index	IP 00
Safety class (prepared)	I
Short circuit strength	non-short-circuit proof
Test voltage	1500 Vac, 50 Hz
Order numbers	
Order Number	AÜ 100/6 Discontinued line - not for new designs



### Mechanical data

Type	AÜ 100/6 Discontinued line - not for new designs
Terminal and mounting	
Fixing method	Hood
Terminals	Solder tab
Measures and weights	
Weight	0.39 kg

