

## Metal enclosures BGUK 2



Picture shows BGUK 30/2

### Advantages

Integrated rail system for the installation of different product sizes (BGUK 30 - BGUK 60)
Excellent corrosion protection and high abrasion resistance through powder-coated surface RAL 5008
Ventilation openings for optimized cooling
Faceplate without cooling fins for individual connection options (BGUK 10 - 60)
Integrated crane eyes

### Applications

Universal metal enclosure with cooling fins for degree of protection IP20/IP23

### Approvals



## Metal enclosures BGUK 2

Type		BGUK 2
Electrical data	Operating data	
	Enclosure suitable for protection index	IP 20
	For power (single-phase)*	250 VA
	For power (three-phase)*	160 VA
	Max. Power loss (at 40 °C ambient temperature)	17 W
Notes		
*		The indicated power is a guideline. Deviations may occur depending on the version of the transformer.
Order numbers		
Order Number		BGUK 2

Type		BGUK 2
Mechanical data	Terminal and mounting	
	Floor mounting	No
	Wall mounting	Yes
	Cable glanding type	2x PG 11
	Cable glanding Ø	5 - 10 mm
	Measures and weights	
	Effective inside dimension (W)	170 mm
	Effective inside dimension (D)	155 mm
	Effective inside dimension (H)	170 mm
	Fixing hole Ø	5.5 mm
Weight	2.7 kg	

