

Metal enclosures **BGUK 60**



Picture shows BGUK 30/2

Advantages

Integrated rail system for the installation of different product sizes (BGUK 30 - BGUK 60)
Excellent corrosion protection and high abrasion resistance through powder-coated surface RAL 5008
Ventilation openings for optimized cooling
Faceplate without cooling fins for individual connection options (BGUK 10 - 60)
Integrated crane eyes

Applications

Universal metal enclosure with cooling fins for degree of protection IP20/IP23

Approvals



Metal enclosures BGUK 60

Type		BGUK 60
Electrical data	Operating data	
	Enclosure suitable for protection index	IP 23
	For power (single-phase)*	25,000 VA
	For power (three-phase)*	25,000 VA
	Max. Power loss (at 40 °C ambient temperature)	950 W
Notes		
*		The indicated power is a guideline. Deviations may occur depending on the version of the transformer.
Order numbers		
Order Number		BGUK 60

Type		BGUK 60
Mechanical data	Terminal and mounting	
	Floor mounting	Yes
	Wall mounting	Yes
	Cable glanding type	2 x M 50
	Cable glanding Ø	23 - 32 mm
Measures and weights		
Effective inside dimension (W)	805 mm	
Effective inside dimension (D)	525 mm	
Effective inside dimension (H)	690 mm	
Fixing hole Ø	13 x 17 mm	
Weight		
Weight	65.0 kg	

