Safety isolating transformer **RKD 15/2x6**



Standards

Safety isolating transformer to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6, UL 5085-1/-2, CSA 22.2 No.66

Advantages

Minimum size at high power

Low weight

Dual input and dual output voltage for series or parallel connection

Minimal no-load losses

Outstanding temperature behaviour thanks to low magnetic leakage field

Applications


Very low noise field

As a mains transformer for adjustment of the voltage and simple electrical isolation.

As an isolating transformer for the safe electrical isolation of the input and output sides. The transformer may be used to set up protective separation as a protective measure in accordance with VDE 0100.

As a safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and $\ensuremath{\mathsf{PELV}}$ circuits because of the limit on the output voltage.

Sample application



Series connection (230V): violet with white

SEC:

PRI

Parallel connection: red with gresy/black with orange Series connection: black with grey





UL 5085-1/-2, CSA 22.2 No.66



BLOCK Transformatoren-Elektronik GmbH · Phone +49 4231 678-0 · info@block.eu



Safety isolating transformer **RKD 15/2x6**

| Туре | RKD 15/2x6 | | Туре | RKD 15/2x6 |
|---|------------------------------|---------------------------------------|--|--------------------------|
| Input | | 30 | Terminal and mounting | |
| Rated input voltage | 2 x 115 Vac | · · · · · · · · · · · · · · · · · · · | Fixing method | Mounting kit, M4 bolt |
| Rated frequency | 50 - 60 Hz | | Terminals | Connecting leads, 200 mm |
| Output Rated output voltage | | data | Measures and weights | |
| Rated output voltage | 2 x 6 Vac | q | Major diameter Ø | 58 mm |
| Rated Power | 15 VA | <u>a</u> | Outside diameter in the area of the wire lead $\ensuremath{\emptyset}$ | 60 mm |
| No-load voltage (app. x factor) | 1.35 | .e | Height without mounting | 27 mm |
| No-load loss (typ.) | 0.30 W | Jai | Weight | 0.29 kg |
| Rated Power No-load voltage (app. x factor) No-load loss (typ.) Efficiency | 73.0 % | | | |
| Standards | | Mechanical | | |
| Classification | Safety isolating transformer | | | |
| Approvals | | | | |
| Approvals | cURus | | | |
| Environment | | | | |
| Ambient temperature max. | 40 °C | | | |
| Safety and protection | | | | |
| Туре | Open type | | | |
| Insulation class | VDE=B, UL=class 105 | | | |
| Protection index | IP 00 | | | |
| Safety class (prepared) | ll | | | |
| Short circuit strength | non-short-circuit proof | | | |
| Test voltage | 4,000 Vac, 50 Hz | | | |
| Order numbers | | | | |
| Order Number | RKD 15/2x6 | | | |